RaptUre Tech™ Pvt. Ltd

PRODUCT DESCRIPTION

- High speed microcontroller based digital design
- Easy to use table top light weighted modal
- S.S 304 and MS powder coated cabinet
- S.S 304 vibrating tool for rust free long life operation
- S.S handle for easy trasportation(optional)
- Qualified for over heat burning
- Fully designed as per the NDDB norms
- IR SENCER BASED FOR AUTOMATIC START AND STOP Function (operation)





Rapture Tech™ Pvt. Ltd

TECHNICAL SPECIFICATIONs



- 230v ac +10%,50hz and 12v dc operated
- Surge protected Transformer or SMPS base power supply
- EMI,high voltage surges & transient protection
- Power consumption 25 to 50w
- Long life ultrasonic ceramic transducer
- Transducer frequency 20khz
- Frequency adjustable up to +2khz
- 2 digit bright led display for user friendly operation
- 1-40 sec adjustable timer from keypad
- 0-80 c operating temperature
- Humidity up to 90% non-condensing
- Weight =4kg



Paras R. Dave

+91 9374672571 paras@rapturetech.co.in www.rapturetech.co.in

GSTIN : 24AAMCR6621D1ZI

29/ A, Keshavbaug Colony, Kothari Tower Road, Opp. Jaina Mangal Society, Ramnagar, Sabarmati, Ahmedabad - 380005